

SPECIAL HOUSING FOR FILTER



HOLDER A-BIG SERIES

Series A-Big, line two-piece containers for cartridges of medium size, suitable to treat major consumption d 'water. It is offered in sizes from 9 "3/4 - 20", is made with vase opaque (pp loaded) and transparency (san blueed). Tested with female threading without brass inserts and air vent in plastic, all done in black PP with provision for wall mounting. All containers are designed to filter cartridges with a diameter of 4.5 effective measures 9 "3/4-20". All containers come without cartridges, with black heads and white or transparent vase. On request and for quantities other colors are also available.

construction characteristics

Hidraulic connection
Sump
O-ring

1" F o 1 1/2" F
Transparent SAN or BLU
NBR

technical data

Temperature of work
Capacity of the filter chartridge without
Pressure of work
Dimensions (mm) AxB

1-50 °C
1"-107 lt/min 1 1/2" - 194,5 lt/min
max 8 bar
9 3/4" - 185x315 20"- 185x625



HOLDER A-NET SERIES

Designed for vertical installations, has the entry at the bottom and the outlet at the top. Suitable to handle low flow rates and reduced dimensions, can be applied to the connecting pipes, pressure washers, beverage dispensers.

HOLDER A-KID SERIES

Able to deal with medium capacity while compact size, the headboard has three attacks, thus allowing both the assembly line to the team according to the different needs of space.

construction characteristics


Hidraulic connection
Sump
O-ring

3/4" F (A-NET) 1/2" F brass (A-KID)
SAN trasparente
NBR

technical data

Temperature of work
capacity of the filter chartridge without
Pressure of work
Dimensions (mm) AxB

1-50 °C
3/4"-60 lt/min (A-NET)
1/2" - 114 lt/min (A-KID)
max 8 bar
A-NET 3/4" - 60X141
A-KID 1/2" - 98X176



HOLDER A-MINI SERIES

They are the smallest containers for cartridges and thanks to the unique shape of the head is also possible to apply directly to the wall.

They are particularly suitable for treatment of pre-filtration and filtration of small appliances, technical equipment and installations where the demand for water is minimal.

Cartridges are available in the network washable nylon (50 microns) and felt extruded (10 microns)



CARTRIDGES FOR FILTRATION

Cartridge mod. GREEN BOO

The cartridges series Green Boo are constructed from extruded polypropylene pure and are considered depth filters multi-layer. The density of extrusion is increasing from the outside inwards, so as to ensure the uniform use of the filtering body. The Green Boo cartridges can combine quality and good cost / effectiveness ratio to provide excellent filtering result. Thanks to the certifications produced, these cartridges are suitable for the removal of sediment content in drinking water for technical purposes and for residential and commercial use.

•Lengths	5", 9"3/4, 10", 20", 30", 40"
•Internal diameter	28 mm
•External diameter	63 mm
•nominal filtration	1 - 5 - 10 - 25 - 50 micron
•Max operative temperature	52°C
•Pressure of work recommended	1,5 kg/cm





Certifications.

NSF 42 standard, FDA approved, ISO 9001 certified, Pure Polypropylene construction.

CARTRIDGE WITH MEMBRANE IN POLIETEROSULFONE PLEATED

These filter cartridges, for their conformation and structure guarantee: quality, efficiency and savings. Thanks to their special characteristics, are used in various sectors: **water treatment, electronic/nucleare, biotechnologies/fine chemistry, food/beverage, paints/coatings, pharmaceutical/cosmetics, petrolchemistry, general industry.**

TIPE OF ATTACKS

DOE		3/22 O-RING/FLAT		8/22 O-RING/SPEAR		7/26 O-RING/FLAT	
							
OPZ. O-RING	COD.	OPZ. O-RING	COD.	OPZ. O-RING	COD.	OPZ. O-RING	COD.
SILICONE	S	SILICONE	S	SILICONE	S	SILICONE	S
EPR	P	EPR	P	EPR	P	EPR	P
BUNA	B	BUNA	B	BUNA	B	BUNA	B
VITON	V	VITON	V	VITON	V	VITON	V

•Lengths	9"3/4, 10", 20", 30", 40"
•Internal diameter	27,9 mm
•External diameter	68,6 mm
•ABSOLUTE filtration	0,1 - 0,2 - 0,45 micron
•Max operative temperature	80°C
•MAX pressure of work	6 bar

Cartridge washable in Nylon RLA

MICRON	HEIGHT	QT./Box	KG/Box	VOL./Box
80	5"	30	12,60	0,030
80	7"	15	8,74	0,030
80	9"3/4	15	12,50	0,030

Cartridge washable in stainless steel

MICRON	HEIGHT	QT./Box	KG/Box	VOL./Box
80	9"3/4	15	12,50	0,030
80	20"	15	6,84	0,035

Cartridges for AQUA BIG

The Big-series filter cartridge is constructed from multi-layers of depth. The Big-Filter, with its high dirt holding capacity and high filtration surface, can reduce the frequency of replacement.

- construction material	: 100% polipropilene	- Lengths	: 10"-20"-30"-40"
- Internal diameter	: 28 mm	- External diameter	: 110 mm
- Filtration (micron)	: 0,5-1-5-10-25-50	- Max operative pressure:	3,2 kg/cmq - 20°C
- Recommended pressure	: 1,5 kg/cmq - 20°C	- Max operative temp.	: 52 °C

Approved FDA, Certificate ISO 9001.